



系列 Series	钢管外径 Tube φ O.D.	M	公称压力 Min. W.P. (bar)	最大工作压力 Max. W.P. (bar)	S1	S2	S3	L1	l1	L2	l2	重量 克/件 Wt. g/p	订货代号 Order No.
L	06	M12x1.5	315	500	17	14	17	22	7.0	42	27.0	61	DV06L
	08	M14x1.5	315	500	19	17	19	23	8.0	42	27.0	84	DV08L
	10	M16x1.5	315	500	22	19	22	25	10.0	43	28.0	109	DV10L
	12	M18x1.5	315	400	24	22	24	25	10.0	44	29.0	136	DV12L
	15	M22x1.5	315	400	27	27	30	27	12.0	46	31.0	222	DV15L
	18	M26x1.5	315	400	32	32	36	30	13.5	49	32.5	334	DV18L
	22	M30x2	160	250	36	36	41	33	16.5	51	34.5	430	DV22L
	28	M36x2	160	250	41	41	46	35	18.5	52	35.5	566	DV28L
	35	M45x2	160	250	50	50	55	40	18.5	58	36.5	858	DV35L
	42	M52x2	160	250	60	60	65	42	19.0	59	36.0	1236	DV42L

S	06	M14x1.5	630	900	19	17	19	27	12.0	44	29.0	103	DV06S
	08	M16x1.5	630	900	22	19	22	28	13.0	44	29.0	132	DV08S
	10	M18x1.5	630	900	24	22	24	31	14.5	46	29.5	179	DV10S
	12	M20x1.5	630	900	27	27	27.5	31	14.5	47	30.5	216	DV12S
	14	M22x1.5	630	700	30	30	31.0	35	17.0	50	32.0	296	DV14S
	16	M24x1.5	400	630	32	32	30.5	35	16.5	50	31.5	343	DV16S
	20	M30x2	400	630	41	41	34.5	39	17.5	55	33.5	569	DV20S
	25	M36x2	400	630	46	46	37.0	44	20.0	59	35.0	922	DV25S
	30	M42x2	400	420	50	50	41.5	48	21.5	64	37.5	1106	DV30S
	38	M52x2	315	420	65	65	43.0	53	22.0	68	37.0	1805	DV38S

不带螺母和卡套时的订货代号示例: DV10LX

如需不锈钢接头订货代号示例: DV10L71

Code example for order without nut and ferrule: DV10LX

Code example for order with stainless steel fitting: DV10L71