



系列 Series	钢管外径 Tube φ O.D.	无缝钢管 Seamless steel tube st37.4	最大工作压力 Max. W.P. (bar)	S1	S2	L	L1	D	D1	O型圈 O-Ring	重量 克/件 Wt. g/p	订货代号 (直通法兰体) Order No. (Directy way flange)
S	10	10x1.0	249	19	22	58.0	10.0	10	8	OR8.0X1.5	75	D10S-H10X1.0
	10	10x1.5	358	19	22	58.0	10.0	10	7	OR8.0X1.5	80	D10S-H10X1.5
	10	10x2.0	460	19	22	58.0	10.0	10	6	OR8.0X1.5	85	D10S-H10X2.0
	12	12x1.5	305	22	24	63.0	15.0	12	9	OR10.0X1.5	102	D12S-H12X1.5
	12	12x2.0	393	22	24	63.0	15.0	12	8	OR10.0X1.5	105	D12S-H12X2.0
	12	12x2.5	476	22	24	63.0	15.0	12	7	OR10.0X1.5	110	D12S-H12X2.5
	16	16x1.5	234	27	30	73.5	16.5	16	13	OR13.0X2.0	154	D16S-H16X1.5
	16	16x2.0	305	27	30	73.5	16.5	16	12	OR13.0X2.0	177	D16S-H16X2.0
	16	16x2.5	372	27	30	73.5	16.5	16	11	OR13.0X2.0	190	D16S-H16X2.5
	16	16x3.0	435	27	30	73.5	16.5	16	10	OR13.0X2.0	204	D16S-H16X3.0
	20	20x2.0	249	32	36	83.5	19.0	20	16	OR16.3X2.4	301	D20S-H20X2.0
	20	20x2.5	305	32	36	83.5	19.0	20	15	OR16.3X2.4	296	D20S-H20X2.5
	20	20x3.0	358	32	36	83.5	19.0	20	14	OR16.3X2.4	302	D20S-H20X3.0
	20	20x4.0	460	32	36	83.5	19.0	20	12	OR16.3X2.4	327	D20S-H20X4.0
	25	25x3.0	294	41	46	92.5	19.5	25	19	OR20.3X2.4	572	D25S-H25X3.0
	25	25x4.0	379	41	46	92.5	19.5	25	17	OR20.3X2.4	559	D25S-H25X4.0
	25	25x5.0	460	41	46	92.5	19.5	25	15	OR20.3X2.4	589	D25S-H25X5.0
	30	30x3.0	249	46	50	101.5	23.0	30	24	OR25.3X2.4	647	D30S-H30X3.0
	30	30x4.0	323	46	50	101.5	23.0	30	22	OR25.3X2.4	691	D30S-H30X4.0
	30	30x5.0	393	46	50	101.5	23.0	30	20	OR25.3X2.4	739	D30S-H30X5.0
	30	30x6.0	460	46	50	101.5	23.0	30	18	OR25.3X2.4	791	D30S-H30X6.0
	38	38x4.0	261	55	60	108.0	22.0	38	30	OR33.3X2.4	1005	D38S-H38X4.0
	38	38x5.0	319	55	60	108.0	22.0	38	28	OR33.3X2.4	1062	D38S-H38X5.0
38	38x6.0	375	55	60	108.0	22.0	38	26	OR33.3X2.4	1129	D38S-H38X6.0	
38	38x7.0	429	55	60	108.0	22.0	38	24	OR33.3X2.4	1205	D38S-H38X7.0	

订货代号示例: D10S-H10X1.0

如需不锈钢接头订货代号示例: D10S-H10X1.071

Order code example: D10S-H10X1.0

Code example for order with stainless steel fitting: D10S-H10X1.071