



系列 Series	钢管外径 Tube φ O.D.	G	最大工作压力 Max. W.P. (bar)	S1	S2	S3	L1	l1	l2	l2	d	l	h	重量 克/件 Wt. g/p	订货代号 Order No.
L	06	M10x1	315	17	14	17	24.0	10.5	27	12.0	14	8	2.5	65	DH06L-PMQKD
	08	M12x1.5	315	19	17	22	30.0	14.0	29	14.5	17	12	3.0	114	DH08L-PMQKD
	10	M14x1.5	315	19	19	22	30.0	14.0	30	15.5	19	12	3.0	126	DH10L-PMQKD
	12	M16x1.5	315	24	22	27	36.0	16.5	33	18.0	21	12	3.0	209	DH12L-PMQKD
	15	M18x1.5	315	30	27	30	39.5	18.5	37	21.5	23	12	3.0	290	DH15L-PMQKD
	18	M22x1.5	315	30	32	32	45.0	21.5	37	21.0	27	14	4.5	394	DH18L-PMQKD
	22	M26x1.5	160	36	36	41	53.0	24.0	44	27.5	31	16	3.5	661	DH22L-PMQKD
	28	M33x2	160	46	41	50	66.0	30.5	49	32.0	39	18	3.5	1116	DH28L-PMQKD
	35	M42x2	160	55	50	60	76.0	35.5	58	36.0	49	20	3.5	1670	DH35L-PMQKD
	42	M48x2	160	60	60	70	87.0	40.5	63	40.5	55	22	3.5	2457	DH42L-PMQKD
S	06	M12x1.5	400	19	17	22	30.0	14.0	31	16.5	17	12	3.0	123	DH06S-PMQKD
	08	M14x1.5	400	19	19	22	30.0	14.0	31	16.5	19	12	3.0	132	DH08S-PMQKD
	10	M16x1.5	400	24	22	27	36.0	16.5	35	18.5	21	12	3.0	220	DH10S-PMQKD
	12	M18x1.5	400	27	24	27	39.5	18.5	36	20.0	23	12	3.0	283	DH12S-PMQKD
	14	M20x1.5	400	30	27	32	43.5	20.0	40	22.5	25	14	3.0	382	DH14S-PMQKD
	16	M22x1.5	400	30	30	32	45.0	21.5	40	22.0	27	14	4.5	398	DH16S-PMQKD
	20	M27x2	250	36	36	41	53.0	24.0	48	26.5	32	16	3.5	712	DH20S-PMQKD
	25	M33x2	250	46	46	50	66.0	30.5	56	31.5	39	18	3.5	1272	DH25S-PMQKD
	30	M42x2	250	55	50	60	76.0	35.5	64	37.0	49	20	3.5	1811	DH30S-PMQKD
	38	M48x2	250	60	60	70	87.0	40.5	72	41.5	55	22	3.5	2679	DH38S-PMQKD

不带螺母和卡套时的订货代号示例: DH10L-PMQKDX

如需不锈钢接头订货代号示例: DH10L-PMQKD71

Code example for order without nut and ferrule:DH10L-PMQKDX

Code example for order with stainless steel fitting:DH10L-PMQKD71