



系列 Series	钢管外径 Tube φ O.D. D1	G	公称压力 Min. W.P. (bar)	最大工作压力 Max. W.P. (bar)	L	l1	l2	l	D	S1	S2	S3	O型圈 O-Ring	重量 克/件 Wt. g/p	订货代号 Order No.
L	06	M10x1	315	420	29	14	20	7	15	14	14	14	OR8X1.88	66	2D06L-PMOD
	08	M12x1.5	315	420	31	16	22	9	18	17	14	17	OR9.4X2.1	66	2D08L-PMOD
	10	M14x1.5	315	420	32	17	24	9	20	19	19	19	OR11.4X2.1	87	2D10L-PMOD
	12	M16x1.5	315	420	34	19	25	9	23	22	19	22	OR13.4X2.1	95	2D12L-PMOD
	15	M18x1.5	315	420	36	21	31	11	25	27	22	24	OR15.54X2.62	224	2D15L-PMOD
	18	M22x1.5	250	400	40	24	33	12	28	32	27	27	OR19.2X3	284	2D18L-PMOD
	22	M27x2	160	250	44	28	36	14	33	36	30	32	OR23.47X2.95	534	2D22L-PMOD
	28	M33x2	160	250	47	31	39	14	41	41	36	41	OR28X3.15	609	2D28L-PMOD
	35	M42x2	160	250	59	38	49	14	51	50	50	50	OR37.69X3.53	844	2D35L-PMOD
	42	M48x2	160	250	61	38	50	16	56	60	50	55	OR42.5X3.15	928	2D42L-PMOD
S	06	M12x1.5	315	500	30	15	22	10	18	17	14	17	OR9.4X2.1	72	2D06S-PMOD
	08	M14x1.5	315	500	32	17	26	10	20	19	19	19	OR11.4X2.1	88	2D08S-PMOD
	10	M16x1.5	315	500	34	18	27	11	23	22	19	22	OR13.4X2.1	97	2D10S-PMOD
	12	M18x1.5	315	500	38	22	31	12	25	24	22	24	OR15.54X2.62	227	2D12S-PMOD
	16	M22x1.5	250	400	43	25	36	14	28	30	27	27	OR19.2X3	286	2D16S-PMOD
	20	M27x2	250	400	49	28	39	16	33	36	30	32	OR23.47X2.95	553	2D20S-PMOD
	25	M33x2	160	250	54	30	44	16	41	46	36	41	OR28X3.15	722	2D25S-PMOD
	30	M42x2	160	250	62	36	51	17	51	50	50	50	OR37.69X3.53	932	2D30S-PMOD
	38	M48x2	160	250	65	34	54	19	56	60	50	55	OR42.5X3.15	1042	2D38S-PMOD

不带螺母和卡套时的订货代号示例: 2D10L-PMODX

Code example for order without nut and ferrule: 2D10L-PMODX